

valid from 1.10.2010

review 1.1.2012

|                      |                           |                                                            |
|----------------------|---------------------------|------------------------------------------------------------|
| <b>PRODUCT NAME:</b> |                           | <b>DECOR</b>                                               |
| <b>APPLICATION:</b>  |                           | <b>LANDSCAPING</b>                                         |
| <b>MATERIAL:</b>     | <b>PILE:</b>              | PE monofilament – mild lens profil (straight + texturized) |
|                      | <b>PRIMARY BACKING:</b>   | 100% PP                                                    |
|                      | <b>SECONDARY BACKING:</b> | SBR Latex                                                  |
| <b>GAUGE:</b>        |                           | 3/8"                                                       |
| <b>COLOR:</b>        |                           | bicolor green                                              |

| PROPERTIES                       | UNIT                | TYPICAL VALUE | TOLERATION |
|----------------------------------|---------------------|---------------|------------|
| Pile fineness                    | [dtex]              | 13.200/16     | ± 5%       |
| Pile width                       | [mm]                | 0,9           | ± 10%      |
| Pile thickness                   | [µm]                | 170           | ± 10%      |
| Pile weight per unit area        | [g/m <sup>2</sup> ] | 1.166         | ± 10%      |
| Stitch rate per 10 cm (length)   | [-/ 10 cm]          | 16            | ± 1        |
| Number of tufts/ m <sup>2</sup>  | [-/m <sup>2</sup> ] | 16.798        | ± 5%       |
| Number of piles/ m <sup>2</sup>  | [-/m <sup>2</sup> ] | 537.536       | ± 5%       |
| Pile height                      | [mm]                | 23            | ± 10%      |
| Weight primary backing           | [g/m <sup>2</sup> ] | 172           | ± 10%      |
| Weight secondary backing         | [g/m <sup>2</sup> ] | 700           | ± 10%      |
| Total weight                     | [g/m <sup>2</sup> ] | 2.038         | ± 10%      |
| Turf withdrawal force            | [N]                 | > 30          |            |
| UV stabilisation ( QUV – lamp A) | [h]                 | 3.000         |            |
| Color fastness – gray scale      | Scale               | ≥ 4           |            |
| Stand. roll width                | [m]                 | 4,00; 2,00    | ± 0,02     |

## COMMENTS:

**Recommended infill:** non filled

In case of free installation without mechanical fixing or bonding may the turf due to climatic changes shrink up to 1%.

Any supplementary information and certificates are available upon request at our sales department.  
According to the Directive 76/ 769 this product does not contain any dangerous substances.